

PACCAR ENGINES

Powered By Quality

OIL SPECIFICATIONS

	EPA10 & EPA13					EPA17				
	5W40	10W40	15W40	5W30	10W30	5W40	10W40	15W40	5W30	10W30
PX-7	J,K	-	J,K	-	J,K	J,K	-	J,K	-	J,K
PX-9	J,K	-	J,K	-	J,K	J,K	-	J,K	-	J,K
MX-11	J,K	J,K	J,K	J,K	J,K	K	J,K	K	K	K
MX-13	J,K	J,K	J,K	J,K	J,K	K	J,K	K	K	K

Recommended
 Approved
 Not Approved

K: CK-4 | **J:** CJ-4

If using the J oil in EPA 2017, must use EPA service intervals.

PACCAR MX ENGINE MAINTENANCE INTERVALS

	MAINTENANCE ITEM	MILES EPA 13	MILES EPA 17	KILOMETERS EPA 13	KILOMETERS EPA 17
Oil and Filter	Severe / Vocational Duty	25,000	30,000	40,000	48,000
	Normal / Line Haul > 20% Idle Time	40,000	50,000	64,000	80,000
	Normal / Line Haul < 20% Idle Time	60,000	75,000	96,000	120,000
Fuel Filter	Severe / Vocational Duty	25,000	30,000	40,000	48,000
	Normal / Line Haul > 20% Idle Time	40,000	50,000	64,000	80,000
	Normal / Line Haul < 20% Idle Time	60,000	75,000	96,000	120,000
Coolant Filter	Severe / Vocational Duty	160,000	300,000	256,000	480,000
	Normal / Line Haul > 20% Idle Time	180,000	300,000	288,000	480,000
DEF Filter		300,000	300,000	480,000	480,000

For complete information see owners manual.