

## P0110

### Fault code description

Inlet air temperature in inlet manifold - Data erratic, intermittent or incorrect at ignition on

### Possible cause

1. Contact resistances in the wiring between the intake air temperature sensor and the ECU
2. Faulty connector
3. Faulty sensor

### Additional information

Sensor value compared to a corrected average engine power up temperature

### Set condition of fault code

This diagnostic starts when the ignition is switched on after the engine was switched off for at least three hours.

### Reset condition of fault code

This fault code will change to inactive immediately after the diagnostic runs and passes.

M028512 - 07/22/2015 19:16:00

This information applies exclusively to the entered chassis number or the selected engine type. Please take into account that this information may change daily. Therefore the provided information is only valid on 12-12-2015. You cannot derive any rights from the information provided with respect to vehicles and/or components of another series, with another chassis number, and/or of another date. ( / )

## P0110, Diagnostic information

Technical data

["Sensor, boost temperature \(F804\)"](#)

Location of component(s)

["Location information, PMCI-2"](#)

Electrical diagram(s)

["PMCI-2"](#)

Description of component(s)

["Boost temperature sensor \(F804\)"](#)

Block diagram

["PMCI-2"](#)

### Step by step troubleshooting



Please perform the troubleshooting steps below by utilising the breakout harness if necessary to check electrical components such as sensors, electrical control units or harnesses. Back probing is not recommended as it could damage the harness. The ignition should always be in the **OFF** position when connecting or disconnecting electrical components to reduce the likelihood of damage to electrical components.



- This troubleshooting tree is based on the assumption that supply power and earth to the PMCI are functioning properly.
- Disconnecting the PMCI connectors during the troubleshooting process will result in multiple errors.
- For specific electrical component information and pin out locations, always refer to the technical data in Rapido.

- It is necessary to exit the 'active errors' screen in DAVIE and run the diagnostic test again to identify a change in errors.
- Remember that the truck's operational or mechanical issues may be the root cause of both active and inactive codes. Refer to the 'possible causes' section in Rapido.

## Step by step 1: Visual Inspections

### Step 1A: Check connections and wiring

#### Troubleshooting steps

1. Visually inspect the component connections and wiring.

#### Are any issues found?

- **Yes** – Repair any issues found. Proceed to step 2A.
- **No** – Proceed to step 2A.

## Step by step 2: Resistance

### Step 2A: Check resistance of sensor and wiring

#### Troubleshooting steps

1. Check the resistance of the sensor and wires. See links at the top of this document for resistance values.

#### Is there any issue with resistance?

- **Yes** – Repair any issues found, proceed to step 3.
- **No** – Replace sensor. Proceed to step 3.

## Step by step 3: Validate repair

### Step 3A: Check if the fault code is active

#### Troubleshooting steps

1. Validate the repairs.

Does the fault code become active after validation?

- Yes – Proceed to step 4A.
- No – Troubleshooting completed.

## Step by step 4: Contact PACCAR Engine Support Center

### Step 4A: Assistance

Contact the PACCAR Engine Support Center for further assistance.

M046278 - 07/22/2015 19:14:41

This information applies exclusively to the entered chassis number or the selected engine type. Please take into account that this information may change daily. Therefore the provided information is only valid on 12-12-2015. You cannot derive any rights from the information provided with respect to vehicles and/or components of another series, with another chassis number, and/or of another date. ( / )