

P1335

Fault code description

Crankshaft speed signal - No signal

Possible cause

1. Faulty wiring
2. Faulty connector
3. Faulty sensor
4. Too large an air gap between the crankshaft sensor (F552) and the flywheel

Additional information

Monitoring for loss of the crankshaft speed sensor signal

Set condition of fault code

The PMCI-2 detects a number of consecutive cylinders with at least 1 crankshaft tooth not seen. This diagnostic runs if the engine speed is below 400 rpm.

Reset condition of fault code

This fault code will change to inactive immediately after the diagnostic runs and passes.

M028077 - 07/22/2015 15:04:37

This information applies exclusively to the entered chassis number or the selected engine type. Please take into account that this information may change daily. Therefore the provided information is only valid on 12-13-2015. You cannot derive any rights from the information provided with respect to vehicles and/or components of another series, with another chassis number, and/or of another date. (/)

P1335, Diagnostic information

Technical data

["Sensor, crankshaft \(F552\)"](#)

Location of component(s)

["Location information, PMCI-2"](#)

Electrical diagram(s)

["PMCI-2"](#)

Description of component(s)

["Crankshaft sensor \(F552\)"](#)

Block diagram

["PMCI-2"](#)

Step by step troubleshooting



Please perform the troubleshooting steps below by utilising the breakout harness if necessary to check electrical components such as sensors, electrical control units or harnesses. Back probing is not recommended as it could damage the harness. The ignition should always be in the **OFF** position when connecting or disconnecting electrical components to reduce the likelihood of damage to electrical components.



- This troubleshooting tree is based on the assumption that supply power and earth to the PMCI is functioning properly.
- Disconnecting the PMCI connectors during the troubleshooting process will result in multiple errors.
- For specific electrical component information and pin out locations, always refer to the technical data in Rapido.
- It is necessary to exit the '**active errors**' screen in DAVIE and run the diagnostic test again to identify any change in errors.
- Remember that the truck's operational or mechanical issues may be the root cause of both active and inactive codes. Refer to the 'possible causes' section in Rapido.

Step 1

Visual inspection- Visually inspect all applicable connectors and harnesses for corrosion, damage and rubbing during each step of the diagnostic procedure. Proceed to step 2.

Step 2

With key **OFF**, disconnect the crankshaft sensor from the engine harness and start the engine:

- **If the engine starts** – Proceed to step 3.
- **If engine does NOT start** – Proceed to step by step diagnostic for code P0016.

Step 3

With key **OFF**, disconnect the crankshaft sensor. Measure the resistance between the signal and ground pins of the crankshaft sensor



Resistance values change with temperature

- **If the resistance is acceptable** – Proceed to step 4
- **If the resistance is NOT acceptable** – Replace the sensor and reconnect the harness, then proceed to the verification procedure listed at the end of this document.

Step 4

With key **OFF**, disconnect the engine harness from PMCI. Perform a continuity test on all wires associated with the sensor:

- **If the continuity is acceptable** – Proceed to step 5.
- **If the continuity is NOT acceptable** – Replace engine harness. Reconnect the harness then proceed to the verification procedure listed at the end of this document

Step 5

Inspect connection pins of engine harness, crankshaft sensor and PMCI:

- **If the pins are acceptable** – Proceed to

step 6.

- **If pins are NOT acceptable** – Replace the engine harness. Reconnect the harness then proceed to the verification procedure listed at the end of this document

Step 6

With key **OFF**, reconnect all the harnesses. Turn the key on and reprogram the PMCI:

- **If code is still active**– Proceed to step 7
- **If no code is present** – Proceed to the verification procedure listed at the end of this document.

Step 7

With key **OFF**, disconnect the crankshaft sensor from the engine harness. Crank the engine and use an AC voltmeter to check the voltage between the signal and earth pins of the crankshaft sensor:

- **If the voltage is acceptable** – Proceed to step 9.
- **If the voltage is NOT acceptable** – Proceed to step 8.

Step 8

With key **OFF**, remove the sensor and check for debris or damage:

- **If Debris is found** – Clean the sensor, reinstall and repeat step 8.
- **If Damage is found** – Replace the sensor and repeat step 8.
- **If No Debris or Damage is found** – Proceed to step 9.

Step 9

Inspect the Flywheel for damage through sensor pass-through:

- **If No damage is found** – Proceed to step 10.
- **If Damage is found** – Replace the Flywheel (see Engine Rapido for information on Flywheel replacement) then proceed to the verification procedure listed at the end of this document.

Step 10

Verify correct timing of Crankshaft and Camshaft Gears:

- **If correct** – Proceed to step 11.
- **If not correct** – Check engine timing (see engine Rapido for instructions on timing the engine). Proceed to the verification procedure listed at the end of this document. **If P1335 is still active**- Proceed to step 11.

Step 11

Possible PMCI failure – Contact the Engine Support Center for further instructions on replacement of the PMCI.

Verification procedure

With DAVIE connected and key **ON**, clear the errors. Start the engine and let it idle to verify with DAVIE that the errors do not re-occur

M046478 - 07/22/2015 15:17:19

This information applies exclusively to the entered chassis number or the selected engine type. Please take into account that this information may change daily. Therefore the provided information is only valid on 12-13-2015. You cannot derive any rights from the information provided with respect to vehicles and/or components of another series, with another chassis number, and/or of another date. (/)