

P2239

Fault code description

Lambda - Voltage too high or short circuit to supply

Possible cause

1. VTG stuck in closed position
2. Faulty wiring
3. Faulty connector
4. Faulty sensor

Additional information

-

Set condition of fault code

The PMCI-2 ECU detects that the lambda sensor current is too high during operation of the lambda sensor.

Reset condition of fault code

This fault code will change to inactive immediately after the diagnostic runs and passes.

To validate the repair, switch off the ignition for at least 15 seconds and then switch it on again.

Start the engine and let it idle for 2 minutes. Drive the vehicle until the coolant temperature is at least 70°C [158°F]. Once the minimum target temperature has been reached, proceed at a minimum speed of 80 km/h [50 mph] in the highest gear possible with the engine speed between 1100 and 1500 rpm and set the cruise control. This test is best performed with a loaded vehicle/trailer, but if load is unavailable, turn as many engine power consumers on to produce engine load. Perform this test for roughly 5 to 8 km [3 to 5 miles] or in 3 separate 1.5 km [1 mile] increments if a steady 5 to 8 km [3 to 5 miles] is unachievable. Use a flat road, if possible.

M027744 - 07/22/2015 15:17:23

This information applies exclusively to the entered chassis number or the selected engine type. Please take into account that this information may change daily. Therefore the provided information is only valid on 12-15-2015. You cannot derive any rights from the information provided with respect to vehicles and/or components of another series, with another chassis number, and/or of another date. (/)

P2239, Diagnostic information

Technical data

["Sensor, lambda \(F834\)"](#)

Location of component(s)

["Location information, PMCI-2"](#)

Electrical diagram(s)

["PMCI-2"](#)

Description of component(s)

["Lambda sensor \(F834\)"](#)

Block diagram

["PMCI-2"](#)

Step by step troubleshooting



Please perform the troubleshooting steps below by utilising the breakout harness if necessary to check electrical components such as sensors, electronic control units or harnesses. Back probing is not recommended as it could damage the harness. The ignition should always be in the **OFF** position when connecting or disconnecting electrical components to reduce the likelihood of damage to electrical components.



- This troubleshooting tree is based on the assumption that supply power and earth to the PMCI are functioning properly.
- Disconnecting the PMCI connectors during the troubleshooting process will result in multiple errors.
- For specific electrical component information and pin out locations, always refer to the technical data in Rapido.

- It is necessary to exit the 'active errors' screen in DAVIE and run the diagnostic test again to identify a change in errors.
- Remember that the truck's operational or mechanical issues may be the root cause of both active and inactive codes. Refer to the 'possible causes' section in Rapido.

Step 1: Check for fault codes

Troubleshooting steps

1. Turn the key switch ON.
2. Use DAVIE to check whether the fault code is present.

Is this fault code present as an active fault code?

- **Yes** – Proceed to step 2.
- **No** – Proceed to any other fault codes present.

Step 2: Visual Inspection

Troubleshooting steps

1. Visually inspect the associated component connections and wiring for any of the following:
 - Loose or broken clamps on the air system
 - VGT is stuck closed
 - Moisture or dirt in the connections
 - Damage to the wire harness or insulation
 - ECU connections are damaged or disconnected
 - Battery damage or loose battery terminal(s)
 - Sensor is not correctly installed

Was there evidence of any of the above?

- **Yes** – Proceed to step 3.
- **No** – Clean, adjust, repair, or replace affected components for any issues identified.

Use DAVIE to re-check for the presence of active faults. If this related fault is no longer active, then this issue has been resolved. If this related fault is still active, continue to step 3.

Step 3: Disconnect the lambda sensor (F834) from engine harness.

Troubleshooting steps

1. Measure the resistance between pin 1 and pin 5 of lambda sensor.

Did the meter indicate an open circuit?

- **Yes** – Proceed to step 4.
- **No** – Replace sensor. Proceed to step 5.

Step 4: Disconnect the engine harness connector (C) from the PCI.

Troubleshooting steps

1. Place a jumper between pin 1 and pin 5 of the lambda sensor connector (F834).
2. Measure the resistance between pin 45 and 21 of the C connector of the PCI.

Does the meter indicate an open circuit?

- **Yes** – Troubleshoot engine harness wiring. Make appropriate repairs or replace harness if necessary. Proceed to step 5.
- **No** – Contact the Engine Support Center (ESC) for further assistance.

Step 5: Use DAVIE to re-check for the presence of active faults

Troubleshooting steps

Is the fault code inactive?

- **Yes** — Issue resolved. Proceed to step 6.
- **No** – Contact the Engine Support Center

(ESC) for further assistance.

Step 6: Validate repair

Troubleshooting steps

1. Key the ignition off for at least 15 seconds, then key it on again.
2. Start the engine and let it idle for 2 minutes.
3. Drive the vehicle until the coolant temperature is at least 70°C [158°F].
4. Once the minimum target temperature has been reached, proceed at a minimum speed of 80 km/h [50 mph] in the highest gear possible with the engine speed between 1100 and 1500 rpm and set the cruise control.
5. Perform this test for roughly 5 to 8 km [3 to 5 miles] or in 3 separate 1.5 km [1 mile] increments if a steady 5 to 8 km [3 to 5 miles] is unachievable. Use a flat road, if possible.

M046642 - 07/23/2015 03:10:25

This information applies exclusively to the entered chassis number or the selected engine type. Please take into account that this information may change daily. Therefore the provided information is only valid on 12-15-2015. You cannot derive any rights from the information provided with respect to vehicles and/or components of another series, with another chassis number, and/or of another date. (/)