

P3842

Fault code description

Air shut-off valve - Short circuit to supply

Possible cause

1. A short to supply voltage in the air shut-off valve.
2. A damaged air shut-off valve.

Additional information

Active DPF regeneration will be disabled.

Set condition of fault code

This diagnostic runs continuously at key on.

The EAS-3 ECU detects a short circuit to supply voltage in the air shut-off valve circuit.

Reset condition of fault code

This fault code will change to inactive immediately after the diagnostic runs and passes.

M027975 - 07/23/2015 02:13:17

This information applies exclusively to the entered chassis number or the selected engine type. Please take into account that this information may change daily. Therefore the provided information is only valid on 12-19-2015. You cannot derive any rights from the information provided with respect to vehicles and/or components of another series, with another chassis number, and/or of another date. (/)

P3842, Diagnostic information

Technical data

["Valve, air shut-off \(L071\)"](#)

Location of component(s)

["Location information, EAS-3"](#)

Electrical diagram(s)

Refer to the OEM service manual for more information.

Description of component(s)

["Valve, air shut-off \(L071\)"](#)

Block diagram

["Block diagram EAS-3"](#)

Step by step troubleshooting



Please perform the troubleshooting steps below by utilising the breakout harness if necessary to check electrical components such as sensors, electrical control units or harnesses. Back probing is not recommended as it could damage the harness. The ignition should always be in the OFF position when connecting or disconnecting electrical components to reduce the likelihood of damage to electrical components.



- Disconnecting the EAS connectors during the troubleshooting process will result in multiple errors.
- For specific electrical component information and pin out locations, always refer to the technical data.
- It is necessary to exit the fault code menu in DAVIE and run the diagnostic test again to identify a

change in errors.

- Remember that the truck's operational or mechanical issues may be the root cause of both active and inactive fault codes. Refer to the 'possible causes' section.

Step by step 1: Check fault codes

Step 1A: Check for fault codes

Troubleshooting steps

1. Turn the key switch ON.
2. Use DAVIE to check for fault codes.

Is fault code P3842 inactive?

- **Yes** – Proceed to step 4A
- **No** – Proceed to step 2A

Step by step 2: Check the air shut-off valve and the circuit

Step 2A: Inspect the air shut-off valve and connector pins

Troubleshooting steps

1. Turn the key switch OFF.
2. Disconnect the air shut-off valve from the harness.
3. Inspect the air-shut-off valve harness and connector for:
 1. corroded or dirty pins
 2. damaged pins
 3. pushed back or expanded pins
 4. loose connector
 5. moisture in or on the connector
 6. connector shell damaged
 7. missing or damaged connector seals
 8. wire insulation damage

Dirty or damaged pins/connector?

- **Yes** – A dirty or damaged connection has been detected. Clean, repair or replace the damaged connection or harness if possible
- Proceed to step 4A
- **No** – Proceed to step 2B

Step 2B: Check for a short circuit in the air shut-off valve

Troubleshooting steps

1. Turn the key switch OFF.
2. Disconnect the air shut-off valve from the harness.
3. Check the air shut-off valve resistance.
4. Measure the resistance between the air shut-off valve supply and ground pin.

Is the resistance 7 to 10 ohms?

- **Yes** – Proceed to step 3A
- **No** – Replace the air shut-off valve.
Proceed to step 4A

Step by step 3: Check the EAS-3 unit and the harness

Step 3A: Inspect the EAS-3 unit and the harness connector pins

Troubleshooting steps

1. Turn the key switch OFF.
2. Disconnect the EAS-3 unit from the harness.
3. Inspect the harness and EAS-3 unit connector for:
 1. corroded or dirty pins
 2. damaged pins
 3. pushed back or expanded pins
 4. loose connector
 5. moisture in or on the connector
 6. connector shell damaged
 7. missing or damaged connector

seals

8. wire insulation damage

Dirty or damaged pins/connector?

- **Yes** – A dirty or damaged connection has been detected. Clean, repair or replace the damaged connection or harness if possible
- Proceed to step 4A
- **No** – Proceed to step 3B

Step 3B: Check for a pin-to-pin short circuit in the harness

Troubleshooting steps

1. Turn the key switch OFF.
2. Disconnect the EAS-3 unit from the harness.
3. Disconnect the air shut-off valve from the harness.
4. Check for a pin-to-pin short circuit.
5. Measure the resistance between the air shut-off valve supply pin and all other pins in the harness.

Is the resistance greater than 100k ohms?

- **Yes** – Proceed to step 4A
- **No** – A pin-to-pin short circuit has been detected in the harness. Repair or replace the harness - Proceed to step 4A

Step by step 4: Clear the fault code

Step 4A: Disable the fault code

Troubleshooting steps

1. Connect all components.
2. Operate the system within the 'reset condition of the fault code' found in the fault code information.
3. Use DAVIE to verify if the fault codes are inactive.

Is fault code P3842 inactive?

- **Yes** – Proceed to step 4B
- **No** – Return to the troubleshooting steps.
Proceed to step 1A

If all the steps have been completed and checked again, contact the Engine Support Center for further instructions.

Step 4B: Clear the inactive fault codes

Troubleshooting steps

1. Connect all components
2. Turn the key switch ON.
3. Use DAVIE to clear the inactive fault codes.

Have all the fault codes been cleared?

- **Yes** – Repair complete
- **No** – Troubleshoot any remaining active fault codes

M046789 - 07/23/2015 02:26:01

This information applies exclusively to the entered chassis number or the selected engine type. Please take into account that this information may change daily. Therefore the provided information is only valid on 12-19-2015. You cannot derive any rights from the information provided with respect to vehicles and/or components of another series, with another chassis number, and/or of another date. (/)