

P3960

Fault code description

NOx sensor before catalyst - CAN communication error

Possible cause

1. Open circuit or power supply too low on the NOx before SCR catalyst sensor.
2. Open earth connection on the NOx before SCR catalyst sensor.
3. Open or short circuit to the CAN wiring between the EAS-3 unit and the NOx before SCR catalyst sensor.
4. Interrupted communication between the NOx before SCR catalyst sensor and the EAS-3 unit.
5. A failed NOx before SCR catalyst sensor.
6. A failed EAS-3 unit.

Additional information

No communication or an invalid data transfer has been detected on the CAN connection between the EAS-3 ECU and the NOx before SCR catalyst sensor.

The NOx before catalyst sensor operation is ignored by the EAS-3 unit.

Set condition of fault code

This diagnostic runs continuously when the key switch is in the ON position.

This fault code is set when the EAS-3 unit loses CAN communication with the NOx before SCR catalyst sensor.

Reset condition of fault code

To validate the repair, start the engine and let it idle for one minute.

This fault code will change to inactive immediately after the diagnostic runs and

passes.

M028332 - 07/22/2015 17:01:48

This information applies exclusively to the entered chassis number or the selected engine type. Please take into account that this information may change daily. Therefore the provided information is only valid on 12-19-2015. You cannot derive any rights from the information provided with respect to vehicles and/or components of another series, with another chassis number, and/or of another date. (/)

P3960, Diagnostic information

Technical data

["Sensor, NOx before catalyst \(F844\)"](#)

Location of component(s)

["Location information, EAS-3"](#)

Electrical diagram(s)

Refer to the OEM service manual for more information.

Description of component(s)

["Sensor, NOx before catalyst \(F844\)"](#)

Block diagram

["Block diagram EAS-3"](#)

Step by step troubleshooting



Please perform the troubleshooting steps below by utilising the breakout harness if necessary to check electrical components such as sensors, electrical control units or harnesses. Back probing is not recommended as it could damage the harness. The ignition should always be in the OFF position when connecting or disconnecting electrical components to reduce the likelihood of damage to electrical components.



- Disconnecting the EAS connectors during the troubleshooting process will result in multiple errors.
- For specific electrical component information and pin out locations, always refer to the technical data.
- It is necessary to exit the fault code menu in DAVIE and run the diagnostic test again to identify a

change in errors.

- Remember that the truck's operational or mechanical issues may be the root cause of both active and inactive fault codes. Refer to the 'possible causes' section.

Step by step 1: Check fault codes

Step 1A: Check for fault codes

Troubleshooting steps

1. Turn the key switch ON.
2. Use DAVIE to check for fault codes.

Is fault code P3960 active?

- Yes – Proceed to step 1B
- No – Proceed to step 5A

Step 1B: Check for fault codes

Troubleshooting steps

1. Turn the key switch ON.
2. Use DAVIE to check for fault codes.

Is fault code P3812, P3962, P3963, P3845 or P3984 active?

- Yes – Proceed to step 4A
- No – Proceed to step 2A

Step by step 2: Check the NOx before catalyst sensor and the circuit

Step 2A: Inspect the NOx before catalyst sensor and connector pins

Troubleshooting steps

1. Turn the key switch OFF.
2. Disconnect the NOx before catalyst sensor from the harness.
3. Inspect the NOx before catalyst sensor harness and connector for:

1. Corroded or dirty pins
2. Damaged pins
3. Pushed back or expanded pins
4. Loose connector
5. Moisture in or on the connector
6. connector shell damaged
7. Missing or damaged connector seals
8. Wire insulation damage

Dirty or damaged pins/connector?

- **Yes** – A dirty or damaged connection has been detected. Clean, repair or replace the damaged connection or harness if possible
- Proceed to step 5A
- **No** – Proceed to step 2B

Step 2B: Check the voltage to the NOx before catalyst sensor

Troubleshooting steps

1. Turn the key switch OFF.
2. Disconnect the NOx before catalyst sensor from the harness.
3. Turn the key switch ON.
4. Measure the voltage between the NOx before catalyst sensor supply circuit and return circuit at the NOx sensor harness connector.



Check the voltage at key ON, while cranking the engine and with the engine running at idle.

Is the voltage within 1 VDC of the battery voltage?

- **Yes** – Proceed to step 4A
- **No** – Proceed to step 3A

Step by step 3: Check the battery and the harness

Step 3A: Check the battery connections

Troubleshooting steps

1. Turn the key switch OFF.
2. Check the positive and negative battery terminals.

Are the connections tight and corrosion-free?

- **Yes** – Proceed to step 3B
- **No** – Tighten and/or clean the connections. Refer to the OEM manual. Proceed to step 5A

Step 3B: Check for an open circuit in the battery voltage supply

Troubleshooting steps

1. Turn the key switch OFF.
2. Disconnect the NOx before catalyst sensor from the harness.
3. Turn the key switch ON.
4. Check for an open circuit.
5. Measure the voltage between the NOx before catalyst sensor battery supply pin and the engine block earth.



Check the voltage at key ON, while cranking the engine and with the engine running at idle.

Is the voltage within 1 VDC of the battery voltage?

- **Yes** – An open circuit has been detected in the NOx before catalyst sensor earth circuit. Repair or replace the wiring. Proceed to step 5A
- **No** – An open circuit has been detected in the NOx before catalyst sensor supply circuit. Check for an open circuit, short circuit or blown fuses in the power supply circuit. Repair or replace the wiring/fuse. Proceed to step 5A

Step by step 4: Check the CAN data wiring

Step 4A: Inspect the EAS-3 unit and the harness connector pins

Troubleshooting steps

1. Turn the key switch OFF.
2. Disconnect the EAS-3 unit from the harness.
3. Inspect the harness and EAS-3 unit connector for:
 1. Corroded or dirty pins
 2. Damaged pins
 3. Pushed back or expanded pins
 4. Loose connector
 5. Moisture in or on the connector
 6. connector shell damaged
 7. Missing or damaged connector seals
 8. Wire insulation damage

Dirty or damaged pins/connector?

- **Yes** – A dirty or damaged connection has been detected. Clean, repair or replace the damaged connection or harness if possible
- Proceed to step 5A
- **No** – Proceed to step 4B

Step 4B: Check for an open circuit in the harness

Troubleshooting steps

1. Turn the key switch OFF.
2. Disconnect the EAS-3 unit from the harness.
3. Disconnect the NOx after catalyst sensor from the harness.
4. Check for an open circuit in the CAN wiring
5. Measure the resistance of the CAN high wire between the EAS-3 unit connector

pin and the NOx before catalyst sensor connector pin.

6. Measure the resistance of the CAN low wire between the EAS-3 unit connector pin and the NOx before catalyst sensor connector pin.

Is the resistance less than 10 ohms?

- **Yes** – Proceed to step 4C
- **No** – An open circuit has been detected in the harness. Troubleshoot the wiring harness and all interconnects. Repair or replace the harness - Proceed to step 5A

Step 4C: Check for a pin-to-pin short circuit in the harness

Troubleshooting steps

1. Turn the key switch OFF.
2. Disconnect the EAS-3 unit from the harness.
3. Disconnect the EAS-3 actuator from the harness.
4. Disconnect the NOx sensor before the catalyst.
5. Disconnect the NOx sensor after the catalyst.
6. Disconnect the engine management ECU.
7. Check for a pin-to-pin short circuit in the CAN wiring.
8. Measure the resistance of the CAN high wire between the EAS-3 unit connector pin and all other connector pins in the harness.
9. Measure the resistance of the CAN low wire between the EAS-3 unit connector pin and all other connector pins in the harness.



Disregard any resistance between 50 and 70 ohms between the CAN high

and CAN low pins.

Is the resistance greater than 100k ohms?

- **Yes** – Proceed to step 4D
- **No** – A short circuit has been detected in the harness. Troubleshoot the wiring harness and all interconnects. Repair or replace the harness - Proceed to step 5A

Step 4D: Check for a short circuit to earth in the harness

Troubleshooting steps

1. Turn the key switch OFF.
2. Disconnect the EAS-3 unit from the harness.
3. Disconnect the EAS-3 actuator from the harness.
4. Disconnect the NOx sensor before the catalyst.
5. Disconnect the NOx sensor after the catalyst.
6. Disconnect the engine management ECU.
7. Check for a short circuit to earth in the CAN wiring.
8. Measure the resistance of the CAN high wire between the EAS-3 unit connector pin and earth.
9. Measure the resistance of the CAN low wire between the EAS-3 unit connector pin and earth.

Is the resistance greater than 100k ohms?

- **Yes** – Proceed to step 4E
- **No** – A short circuit to earth has been detected in the harness. Troubleshoot the wiring harness and all interconnects. Repair or replace the harness - Proceed to step 5A

Step 4E: Check the CAN terminating resistance

Troubleshooting steps

1. Turn the key switch OFF.
2. Disconnect the EAS-3 unit.
3. Connect all other components.
4. Check the terminating resistance.
5. Measure the resistance between the CAN high pin and the CAN low pin on the EAS-3 unit connector.

Is the resistance 50 to 70 ohms?

- **Yes** – Return to the troubleshooting steps - Proceed to step 1A

If all the steps have been completed and checked again, replace the NOx sensor before catalyst and proceed to step 5A.

- **No** – Proceed to step 4F

Step 4F: Check the CAN terminating resistance

Troubleshooting steps

1. Turn the key switch OFF.
2. Disconnect the EAS-3 actuator from the harness.
3. Disconnect the EAS-3 unit.
4. Connect all other components.
5. Check the terminating resistance.
6. Measure the resistance between the CAN high pin and the CAN low pin on the EAS-3 unit connector.

Is the resistance 110 to 130 ohms?

- **Yes** – Return to the troubleshooting steps - Proceed to step 1A

If all the steps have been completed and checked again, contact the Engine Support Center for further instructions on replacement of the EAS-3 actuator.

- **No** – End resistance or CAN wiring engine management system not correct.

Troubleshoot the engine management system. Proceed to step 5A

Step by step 5: Clear the fault code

Step 5A: Disable the fault code

Troubleshooting steps

1. Connect all components.
2. Operate the system within the 'reset condition of the fault code' found in the fault code information.
3. Use DAVIE to verify if the fault codes are inactive.

Is fault code P3960 inactive?

- **Yes** – Proceed to step 5B
- **No** – Return to the troubleshooting steps - Proceed to step 1A

If all the steps have been completed and checked again, contact the Engine Support Center for further instructions.

Step 5B: Clear the inactive fault codes

Troubleshooting steps

1. Connect all components
2. Turn the key switch ON.
3. Use DAVIE to clear the inactive fault codes.

Have all the fault codes been cleared?

- **Yes** – Repair complete
- **No** – Troubleshoot any remaining active fault codes

M046907 - 07/23/2015 02:04:54

This information applies exclusively to the entered chassis number or the selected engine type. Please take into account that this information may change daily. Therefore the provided information is only valid on 12-19-2015. You cannot derive any rights from the information provided with respect to vehicles and/or components of another series, with another chassis number, and/or of another date. (/)